



Epoxy Wash

CLEANER FOR EPOXY & ADHESIVE RESIN RESIDUES

- * Strong Acid with NO FUMES * Water Based
- * Industrial Grade Detergent

Epoxy Wash aggressively cleans off epoxy and grout residues that can stain tile surfaces. **Epoxy Wash** is suitable for use over coloured grout joints.

SUITABLE RESIDUES

- ♦ Epoxy Grout
- ♦ Grout Resins

INTERIOR/EXTERIOR

- ♦ Walls & Floors

COLOUR

- ♦ Clear

SUITABLE SUBSTRATES

- ♦ Ceramic & Mosaic Tiles
- ♦ Concrete
- ♦ Plaster
- ♦ Metal Fittings
- ♦ Sinks & Tubs



PRECAUTIONS

Epoxy Wash is unsuitable for:

- ♦ cleaning moisture sensitive green marble;
- ♦ general marble or other calcareous stones;
- ♦ tiles with an acid sensitive glaze.

SPECIAL CARE REQUIRED

Test a small area prior to cleaning the whole tile installation. Residues must be rinsed off surrounding surfaces & metal fittings with water. Spills on fabrics must be rinsed off immediately with water to avoid staining and permanent damage. Always wear rubber gloves and eye protection when working with **Epoxy Wash**. Dispose of all cleaning cloths into a plastic bag and landfill. **Do not pour this product down drains or waterways.**

SURFACE PREPARATION

Protect all surfaces that could be splashed with **Epoxy Wash**. Highly absorbent substrates such as porous ceramic tiles, concrete or plaster must be wet with water before **Epoxy Wash** can be applied.

COVERAGE

Coverage is approximate only and will vary according to the degree of cement residues present on the floor. As a guide, 1 litre of **Epoxy Wash** will clean approximately 10 square metres of floor.

APPLICATION & TOOLS

Apply **Epoxy Wash** with a mop or brush, working within small areas at a time. Allow **Epoxy Wash** to react for about 10 minutes. Scrub the floor with a wet brush or an abrasive sponge, such as a medium-grain SCOTCHBRITE, to remove any crusts or stains that still remain and continue scrubbing until all visible stains have disappeared. Repeat the operation for very persistent crusts or stains. Remove **Epoxy Wash** with an absorbent cloth and then rinse the floor thoroughly and repeatedly with water. Finish the floor by drying it with a cloth.

CLEAN UP

Epoxy Wash can be rinsed off any surface or material with an absorbent cloth and water.

SHELF LIFE

Twelve months if stored in the original factory sealed packaging.

PACKAGING

Epoxy Wash is available in 1L & 5L containers.

SPECIFICATION CLAUSE

The wall & floor cleaner shall be Morgan **Epoxy Wash** - a high performance epoxy residue cleaner.

MORGAN QUALITY POLICY STATEMENT

Epoxy Wash is manufactured and distributed to a quality system based on ISO 9001:2000.



11 Raymond Avenue Bayswater WA 6053
Ph: 08 9272 4666 Fx: 08 9370 1744
www.morganadhesives.com.au

**FREE TECHNICAL ADVICE AND MATERIAL SAFETY
DATA SHEETS**

Email: accounts@morganadhesives.com.au

Technical Helpline: 08 9441 6677 (Response within 24hrs)

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.

