



Grout Seal

CLEAR & SEMI-GLOSS

***Enhances Grout Colour * Solvent Based * Stain Resistant**

Grout Seal is specifically formulated to enhance a grouts original colour and reduce its efflorescence. **Grout Seal** cures to a semi-gloss, easy to maintain & stain resistant finish.

SUITABLE GROUTS

- ◆ All

SUITABLE SUBSTRATES

- ◆ All

COLOUR

- ◆ Clear

INTERIOR

- ◆ Walls & Floors



PRECAUTIONS

Grout Seal is unsuitable for:

- ◆ wet grouts; surfaces to be treated must be thoroughly dry
- ◆ external installations;
- ◆ grouts subject to rising damp or condensation.

SPECIAL CARE REQUIRED

Test a small area prior to sealing the whole tile joint installation. Residues must be rinsed off tiles & surrounding fittings with Solvent TX. Spills on fabrics must be rinsed off immediately with detergent to avoid staining and permanent damage. Always wear rubber gloves and eye protection when working with **Grout Seal**. **DO NOT SMOKE** during application.

GROUT PREPARATION

Grouts must be thoroughly cleaned of all dust and any other contaminants. Use **Grout Seal** on dry tile grouts only.

New Grout Installations: Seal 48 hours after damp curing. Seal 15 days after installing and grouting highly absorbent tiles such as terracotta to avoid trapping any eventual efflorescence on the surface.

Old Grout Installations: Seal 48 hours after cleaning.

COVERAGE

Coverage is approximate only and will vary according to the porosity of the grout. As a guide, 1 litre of **Grout Seal** will cover approximately 8 square metres of floor.

APPLICATION & TOOLS

Grout Seal should be applied undiluted using a brush. A thin application is recommended for best results. Working within small areas at a time, completely wet the grout with **Grout Seal**. Avoid using excess sealer and wipe up any residues after 1 or 2 minutes with a clean cloth. Avoid overlapping the sealer during application. For a more durable finish, apply a second coat of **Grout Seal** after the first coat has completely dried.

CURE TIME

Grout Seal cures in approximately 12 hours at 23°C and 50% relative humidity. Temperatures during sealing below 10°C will significantly increase the cure time. Sealed floors are ready for light traffic after 30 minutes.

CLEAN UP

Wet **Grout Seal** can be cleaned off any surface with a suitable solvent such as Solvent TX.

EXPECTED WEAR

Grout Seal has an approximate wear life of at least 5 years on interior installations.

SHELF LIFE

Twelve months if stored in the original factory sealed packaging.

PACKAGING

Grout Seal is available 20L, 10L, 4L, 1L & 500ML containers.

SPECIFICATION CLAUSE

The grout sealer shall be Morgan **Grout Seal** - an acrylic grout sealer.

MORGAN QUALITY POLICY STATEMENT

Grout Seal is manufactured and distributed to a quality system based on ISO 9001:2000. **Grout Seal** is guaranteed for 5 years when applied in conjunction with written technical information supplied by **Morgan Ceramic Tile Adhesives**.

FREE TECHNICAL ADVICE AND MATERIAL SAFETY DATA SHEETS

Email: accounts@morganadhesives.com.au

Technical Helpline: 08 9441 6677 (Response within 24hrs)

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.

