



Slate Seal

CLEAR & FULL GLOSS

*** Enhances Colour * Solvent Based * Stain Resistant**

Slate Seal is specifically formulated to seal & enhance a stones original colour. **Slate Seal** cures to a full gloss, easy to maintain & stain resistant finish.

SUITABLE STONES

- ♦ Natural Stone
- ♦ Slate

COLOUR

- ♦ Clear

SUITABLE SUBSTRATES

- ♦ All

INTERIOR

- ♦ Walls & Floors

PRECAUTIONS

Slate Seal is unsuitable for:

- ♦ wet stone; area to be treated must be thoroughly dry
- ♦ external installations;
- ♦ installations subject to rising damp or condensation.

SPECIAL CARE REQUIRED

Test a small area prior to sealing the whole tile installation. Residues must be rinsed off tiles & surrounding fittings with Solvent TX. Spills on fabrics must be rinsed off immediately with detergent to avoid staining and permanent damage. Always wear rubber gloves and eye protection when working with **Slate Seal**. **DO NOT SMOKE** during application.

SLATE FLOOR PREPARATION

Stones must be thoroughly cleaned of all dust and any other contaminants. Use **Slate Seal** on dry stone only.

New Slate Installations: Seal 7 days after curing.

Old Slate Installations: Seal 7 days after cleaning.

APPLICATION & TOOLS

Slate Seal should be applied undiluted using a brush. A thin application is recommended for best results. Working within small areas at a time, completely wet the slate with **Slate Seal**. Avoid using excess sealer and wipe up any residues after 1 or 2 minutes with a clean cloth. Avoid overlapping the sealer during application. For a more durable finish, apply a second coat of **Slate Seal** after the first coat has completely dried.

COVERAGE

Coverage is approximate only and will vary according to the porosity of the stone or concrete. As a guide, 1 litre of **Slate Seal** will cover approximately 10 square metres of floor.



CURE TIME

Slate Seal cures in approximately 12 hours at 23° C and 50% relative humidity. Temperatures during sealing below 10°C will significantly increase the cure time. Sealed floors are ready for light traffic after 30 minutes.

CLEAN UP

Wet **Slate Seal** can be cleaned off any surface with Solvent TX.

EXPECTED WEAR

Slate Seal has an approximate wear life of at least 5 years on interior installations.

SHELF LIFE

Twelve months if stored in the original factory sealed packaging.

PACKAGING

Slate Seal is available 20L, 10L, 4L & 1L containers.

SPECIFICATION CLAUSE

The slate sealer shall be Morgan **Slate Seal** - an acrylic slate sealer.

MORGAN QUALITY POLICY STATEMENT

Slate Seal is manufactured and distributed to a quality system based on ISO 9001:2000. **Slate Seal** is guaranteed for 5 years when applied in conjunction with written technical information supplied by **Morgan Ceramic Tile Adhesives**.

FREE TECHNICAL ADVICE AND MATERIAL SAFETY DATA SHEETS

accounts@morganadhesives.com.au

Technical Helpline: 08 9441 6677 (Response within 24hrs)

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.

