



Stone & Concrete Seal

CLEAR & FULL GLOSS

*** Enhances Stone Colour * Solvent Based * Stain Resistant**

Stone & Concrete Seal is specifically formulated to enhance a stones original colour and reduce its efflorescence. **Stone & Concrete Seal** creates a full gloss, easy to maintain & stain resistant finish.

SUITABLE STONES

- ◆ Natural Stone
- ◆ Bicottura
- ◆ Marble
- ◆ Limestone
- ◆ Concrete
- ◆ Adobe Rammed Earth

COLOUR

- ◆ Clear

INTERIOR

- ◆ Walls & Floors

SUITABLE SUBSTRATES

- ◆ All

PRECAUTIONS

Stone & Concrete Seal is unsuitable for:

- ◆ wet stone;
- ◆ external installations;
- ◆ installations subject to rising damp or condensation.

SPECIAL CARE REQUIRED

Test a small area prior to sealing the whole tile installation. Residues must be rinsed off tiles & surrounding fittings with Solvent TX. Spills on fabrics must be rinsed off immediately with detergent to avoid staining and permanent damage. Always wear rubber gloves and eye protection when working with **Stone & Concrete Seal**. **DO NOT SMOKE** during application.

STONE & CONCRETE PREPARATION

Stones must be thoroughly cleaned of all dust and any other contaminants. Use **Stone & Concrete Seal** on dry stone or concrete only.

New Stone & Concrete Installations: Seal 7 days after curing. Seal 15 days after installing highly absorbent tiles such as terracotta to avoid trapping any eventual efflorescence on the surface.

Old Stone & Concrete Installations: Seal 7 days after cleaning.



APPLICATION & TOOLS

Stone & Concrete Seal should be applied undiluted using a brush. A thin application is recommended for best results. Working within small areas at a time, completely wet the stone or concrete with **Stone & Concrete Seal**. Avoid using excess sealer and wipe up any residues after 1 or 2 minutes with a clean cloth. Avoid overlapping the sealer during application. For a more durable finish, apply a second coat of **Stone & Concrete Seal** after the first coat has completely dried.

COVERAGE

Coverage is approximate only and will vary according to the porosity of the stone or concrete. As a guide, 1 litre of **Stone & Concrete Seal** will cover approximately 6 square metres of floor.

CURE TIME

Stone & Concrete Seal cures in approximately 12 hours at 23°C and 50% relative humidity. Temperatures during sealing below 10°C will significantly increase the cure time. Sealed floors are ready for light traffic after 30 minutes.

CLEAN UP

Wet **Stone & Concrete Seal** can be cleaned off any surface with Solvent TX.

EXPECTED WEAR

Stone & Concrete Seal has an approximate wear life of at least 5 years on interior installations.

SHELF LIFE

Twelve months if stored in the original factory sealed packaging.

PACKAGING

Stone & Concrete Seal is available 20L, 10L, 4L & 1L containers.

SPECIFICATION CLAUSE

The stone & concrete sealer shall be Morgan **Stone & Concrete Seal** - an acrylic stone & concrete sealer.

MORGAN QUALITY POLICY STATEMENT

Stone & Concrete Seal is manufactured and distributed to a quality system based on ISO 9001:2000. **Stone & Concrete Seal** is guaranteed for 5 years when applied in conjunction with written technical information supplied by **Morgan Ceramic Tile Adhesives**.

FREE TECHNICAL ADVICE AND MATERIAL SAFETY DATA SHEETS

accounts@morganadhesives.com.au

Technical Helpline: 08 9441 6677 (response within 24hrs)

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.